Dopomat-Xtreme

Industrial floor cleaner for scrubber driers

- Highly alkaline industrial cleaner
- Spontaneous dissolution of industrial soiling, oils and greases
- Mechanical removal of stubborn dirt
- Very low foaming even when used in higher concentrations
- Very good separation characteristics in wastewater
- According to ÖNORM B 5105, Clause 7.2, suitable for oil separators




Area of application

Can be used on water and alkali-resistant surfaces in industry. Not suitable for use on linoleum and rubber floors or on calcite-based stones such as marble or terrazzo tiles.

Application

Please test on a small inconspicuous spot before first application. Adjacent areas and objects must be protected.

Routine cleaning (mechanical wet cleaning):
Depending on the degree of soiling, 100–200 ml to 10 L of cold water. Consumption: 1.0–2.0 ml/m².



Note

Kiehl accepts no liability or responsibility for damage caused as a result of incorrect use or application of the product. Not a consumer product according to 1999/44/EC Art. 1! For professional use only!

Ingredients (according to 648/2004/EC)

Nonionic surfactants < 5%, anionic surfactants < 5%, phosphonates < 5%, alkalis, complexing agents.
pH value (concentrate): approx. 13.5 pH value (ready-to-use solution): approx. 12

Classification

Classification (in concentrate): GHS05, Danger. H314 Causes severe skin burns and eye damage. P280 Wear protective gloves/protective clothing/eye protection/face protection. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 IF exposed or concerned: Get medical advice/attention. Contains: Sodium Hydroxide (INCI)

Art. No.	Packaging unit (PU)	Numbers of PU per pallet
j054010	10 L canister	60
j054072	200 L drum	2

www.kiehl-group.com