Dipex

Stripper

- Active cleaning, low-foaming stripper
- For alkali-resistant floorings
- Removes polymer coatings, release agent films, maintenance films as well as oil and grease
- Alkaline
- Free from butyl glycol



Area of application

Can be used on water and alkali-resistant floorings, such as PVC, granite, porcelain stoneware tiles. Not suitable for use on linoleum and rubber floors or on calcite-based stones such as marble or terrazzo tiles.

Application

Please test on a small inconspicuous spot before first application.

Polymer stripping:
1–3 L to 8 L of cold water.
Distribute the cleaning solution on the floor, leave to react for approx. 10 minutes, scrub, vacuum the dirty solution, rinse thoroughly with clean water. Consumption: 27.8–68.2 ml/m^2.



Note

Kiehl accepts no liability or responsibility for damage caused as a result of incorrect use or application of the product. Not a consumer product according to 1999/44/EC Art. 1! For professional use only!

Ingredients (according to 648/2004/EC)

Nonionic surfactants < 5%, soap < 5%, phosphates < 5%, alkalis, complexing agents, water-soluble solvents, fragrances (Citrus Aurantium Peel Oil, Limonene).
pH value (concentrate): approx. 11.5 pH value (ready-to-use solution): approx. 11

Art. No.	Packaging unit (PU)	Numbers of PU per pallet
j150110	10 L canister	60
j150172	200 L drum	2

www.kiehl-group.com