# Copex

## All-round stripper

- Active cleaning, low-foaming stripper
- Preferably used for alkali-sensitive resilient floorings
- Removes polymer coatings, release agent films, maintenance films as well as oil and grease
- Suitable for cleaning conductive and dissipative surfaces (ESD)
- Free from butyl glycol
- Contains renewable plant-based raw materials




### Area of application

Can be used on water-resistant, alkali-sensitive and alkali-resistant floorings, such as PVC, linoleum, rubber, natural and artificial stone.

### Application

Please test on a small inconspicuous spot before first application.

**Polymer stripping:**
1–3 L to 8 L of cold water.
Distribute the cleaning solution on the floor, leave to react for approx. 10 minutes, scrub, vacuum the dirty solution, rinse thoroughly with clean water. Consumption: 27.8–68.2 ml/m$^2$.



**Note**

Kiehl accepts no liability or responsibility for damage caused as a result of incorrect use or application of the product. Not a consumer product according to (EU) 2019/771 Art. 2! For professional use only!

**Ingredients (according to 648/2004/EC)**

Nonionic surfactants < 5%, soap < 5%, water-soluble solvents, solubilizers, dyes, fragrances.
pH value (concentrate): approx. 9.5 pH value (ready-to-use solution): approx. 9

**Classification**

Classification (in concentrate): GHS07, Warning. H319 Causes serious eye irritation. P280 Wear eye protection. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

| Art. No. | Packaging unit (PU) | Numbers of PU per pallet |
|---|---|---|
| j150401 | Carton of 6 x 1 L PCR bottles | 84 |
| j150410 | 10 L canister | 60 |
| j150472 | 200 L drum | 2 |



www.kiehl-group.com