Veroclean

Express stripper

- Powerful, high-performance stripper for removing polymer layers
- For removing coatings which could previously only be removed partly or not at all
- Capacity to dissolve the polymer coating quickly
- Short reaction time
- Free from butyl glycol
- Contains renewable plant-based raw materials



Area of application

Can be used on water-resistant, alkali-sensitive and alkali-resistant floorings, such as PVC, linoleum, rubber, natural and artificial stone.

Application

Please test on a small inconspicuous spot before first application.

Polymer stripping:
1–3 L to 8 L of cold water.
Distribute the cleaning solution on the floor, leave to react for a short time, scrub, vacuum the dirty solution, rinse thoroughly with water. Consumption: 27.8–68.2 ml/m^2.



Note

Kiehl accepts no liability or responsibility for damage caused as a result of incorrect use or application of the product. Not a consumer product according to 1999/44/EC Art. 1! For professional use only!

Ingredients (according to 648/2004/EC)

Nonionic surfactants < 5%, amphoteric surfactants < 5%, soap < 5%, water-soluble solvents, dyes, fragrances.
pH value (concentrate): approx. 9.5 pH value (ready-to-use solution): approx. 9

Classification

Classification (in concentrate): GHS07, Warning. H315 Causes skin irritation. H319 Causes serious eye irritation. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/eye protection. P302+P352 IF ON SKIN: Wash with plenty of water. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Art. No.	Packaging unit (PU)	Numbers of PU per pallet
j150710	10 L canister	60
j150772	200 L drum	2

www.kiehl-group.com