Copex-eco

All-round stripper

- Active cleaning, low-foaming stripper
- Preferably used for alkali-sensitive resilient floorings
- Removes polymer coatings, release agent films, maintenance films as well as oil and grease
- Free from butyl glycol
- Does not require CLP Regulation markings



Area of application

Can be used on water-resistant, alkali-sensitive and alkali-resistant floorings, such as PVC, linoleum, rubber, natural and artificial stone.

Application

Please test on a small inconspicuous spot before first application.

Polymer stripping:
1–3 L to 8 L of cold water.
Distribute the cleaning solution on the floor, leave to react for approx. 15–20 minutes, scrub, vacuum the dirty solution, rinse thoroughly with clean water. Consumption: 27.8–68.2 ml/m².



Note

Kiehl accepts no liability or responsibility for damage caused as a result of incorrect use or application of the product. Not a consumer product according to 1999/44/EC Art. 1! For professional use only!

Ingredients (according to 648/2004/EC)

Nonionic surfactants < 5%, water-soluble solvents, solubilizers.
pH value (concentrate): approx. 9.5

pH value (ready-to-use solution): approx. 9

Art. No.	Packaging unit (PU)	Numbers of PU per pallet
j150910	10 L canister	60

www.kiehl-group.com