Thermospeed

High-speed emulsion polish

- Self-shining polymer emulsion
- Outstanding film-forming properties
- Particularly hard-wearing, dirt-repelling, wipe-proof and slip resistant
- Very good water resistance
- Resistant to surface disinfectant products
- Easy removal of scuff marks by polishing (approx. 1000 rpm)
- Optimally polishable



Area of application

Can be used on water-resistant, coatable, stripped floorings, e.g. PVC, rubber, linoleum, absorbent natural and artificial stone. Please perform an adhesion test before using on floorings with a PU or PE wear layer.

Application

Please test on a small inconspicuous spot before first application. Do not let the product dry on the mop. Close canister immediately after use. Avoid draughts during use and drying.

Coating:
Depending on the absorbency of the surface, 2–3 applications at intervals of approx. 30 minutes.
Following stripping and a short drying time, apply a thin coat of undiluted product, e.g. using a flat mop or waxer.
Consumption: 25.0 ml/m² per application.

Polishing:
Occasional polishing (approx. 1000 rpm) compacts the care components, removes scuff marks caused by traffic and increases durability.



Note

Kiehl accepts no liability or responsibility for damage caused as a result of incorrect use or application of the product. Not a consumer product according to (EU) 2019/771 Art. 2! For professional use only! Protect from frost.

Ingredients

Synthetic dispersions, hard polyethylene waxes, water-soluble solvents, resins, softeners, preservatives.
pH value (concentrate): approx. 8.5

Classification

Classification (in concentrate): EUH208 Contains Methylisothiazolinone, Methylchloroisothiazolinone. May produce an allergic reaction.

Art. No.	Packaging unit (PU)	Numbers of PU per pallet
j200305	Carton of 2 x 5 L PCR canisters	56

www.kiehl-group.com