Thermodur-satina

Satin-matt all-purpose emulsion polish

- Matt polymer emulsion
- Outstanding film-forming properties
- Particularly hard-wearing, dirt-repelling, wipe-proof and slip resistant
- Very good water resistance
- The matt film does not become shiny, even if polished
- Resistant to surface disinfectant products



Area of application

Can be used on water-resistant, coatable, stripped floorings, e.g. PVC, rubber, linoleum, absorbent natural and artificial stone. Please perform an adhesion test before using on floorings with a PU or PE wear layer.

Application

Please test on a small inconspicuous spot before first application. Shake well before use. Do not let the product dry on the mop. Close canister immediately after use. Avoid draughts during use and drying.

Coating:
Depending on the absorbency of the surface, 2–3 applications at intervals of approx. 30 minutes.
Following stripping and a short drying time, apply a thin coat of undiluted product, e.g. using a flat mop or waxer.
Consumption: 25.0 ml/m² per application.

For routine cleaning, do not use maintenance products, since they can create a shiny effect.



Note

Kiehl accepts no liability or responsibility for damage caused as a result of incorrect use or application of the product. Not a consumer product according to (EU) 2019/771 Art. 2! For professional use only! Protect from frost.

Ingredients

Synthetic dispersions, polyethylene waxes, water-soluble solvents, resins, softeners, preservatives.
pH value (concentrate): approx. 8.5

Classification

Classification (in concentrate): EUH208 Contains Methylisothiazolinone, Methylchloroisothiazolinone. May produce an allergic reaction.

Art. No.	Packaging unit (PU)	Numbers of PU per pallet
j200705	Carton of 2 x 5 L PCR canisters	56

www.kiehl-group.com