Ariston

Polymer-based maintenance cleaner

- Polymer-based maintenance cleaner
- Effective cleaning with increased maintenance element
- Can also be used undiluted for basic care
- Leaves a self-shining, dirt-repellent and non-slip maintenance film



Area of application

Can be used on water-resistant, hard and resilient floorings, e.g. PVC, linoleum, rubber, natural and artificial stone.

Application

Please test on a small inconspicuous spot before first application.

Coating:
Depending on the absorbency of the surface, 1–3 applications at intervals of approx. 60 minutes.
Following stripping and a short drying time, apply a thin coat of undiluted product, e.g. using a flat mop or waxer.
Consumption: 25.0 ml/m².

Routine cleaning (wiping):
Depending on the desired care effect, 100–200 ml to 8 L of cold water. Consumption: 0.4–0.7 ml/m².

Spray buffing:
100 ml to 500 ml of cold water.
Apply using a spray bottle and polishing machine (approx. 150–1000 rpm). Consumption: 1.0 ml/m².



Note

Kiehl accepts no liability or responsibility for damage caused as a result of incorrect use or application of the product. Not a consumer product according to 1999/44/EC Art. 1! For professional use only!

Ingredients (according to 648/2004/EC)

Nonionic surfactants < 5%, polyethylene waxes, polymers, additives, fragrances, preservatives (Sodium Pyrithione, Benzisothiazolinone).
pH value (concentrate): approx. 8.5

Art. No.	Packaging unit (PU)	Numbers of PU per pallet
j300210	10 L canister	60

www.kiehl-group.com